



Peachtree Doors and Windows is a manufacturer of exterior windows, patio doors and entrance doors. This Manufacturer's Certification Statement serves as verification that the Peachtree door and window products listed below qualify for the Energy Tax Credit in accordance with IRS 2006-26 document.

600 Series Fiberglass Clad Products						
Product Line	Grills	Glazing Thickness	Glazing Option	U-Factor	SHGC	Tax Credit
Casement	none	3/4"	Insul Low-e w/ Argon	0.29	0.30	Y
Casement	none	3/4"	Insul Bronze Low-e w/ Argon	0.29	0.29	Y
Casement	none	3/4"	Insul Low-e 240 w/ Argon	0.29	0.19	Y
Casement	none	3/4"	Zo-e-shield 5 w/ Argon	0.28	0.20	Y
Casement	none	3/4"	Zo-e-shield 6 w/ Argon	0.29	0.20	Y
Casement	none	3/4"	Zo-e-shield Coastal w/ Argon	0.29	0.20	Y
Casement	none	1"	Zo-e-shield 7	0.26	0.19	Y
Casement	none	1"	Zo-e-shield 7 w/ Argon	0.22	0.18	Y
Casement	Std GIA/SDL	3/4"	Insul Low-e w/ Argon	0.29	0.28	Y
Casement	Std GIA/SDL	3/4"	Insul Bronze Low-e w/ Argon	0.29	0.26	Y
Casement	Std GIA/SDL	3/4"	Insul Low-e 240 w/ Argon	0.29	0.17	Y
Casement	Std GIA/SDL	3/4"	Zo-e-shield 5 w/ Argon	0.28	0.18	Y
Casement	Std GIA/SDL	3/4"	Zo-e-shield 6 w/ Argon	0.30	0.18	Y
Casement	Std GIA/SDL	3/4"	Zo-e-shield Coastal w/ Argon	0.30	0.18	Y
Casement	Std GIA/SDL	1"	Zo-e-shield 7	0.26	0.17	Y
Casement	Std GIA/SDL	1"	Zo-e-shield 7 w/ Argon	0.23	0.17	Y
Casement	15/16" GIA	3/4"	Insul Low-e w/ Argon	0.29	0.25	Y
Casement	15/16" GIA	3/4"	Insul Bronze Low-e w/ Argon	0.29	0.24	Y
Casement	15/16" GIA	3/4"	Insul Low-e 240 w/ Argon	0.29	0.16	Y
Casement	15/16" GIA	3/4"	Zo-e-shield 5 w/ Argon	0.28	0.17	Y
Casement	15/16" GIA	3/4"	Zo-e-shield 6 w/ Argon	0.30	0.17	Y
Casement	15/16" GIA	3/4"	Zo-e-shield Coastal w/ Argon	0.30	0.17	Y
Casement	15/16" GIA	1"	Zo-e-shield 7	0.26	0.16	Y
Casement	15/16" GIA	1"	Zo-e-shield 7 w/ Argon	0.23	0.16	Y
Awning	none	3/4"	Insul Low-e w/ Argon	0.29	0.30	Y
Awning	none	3/4"	Insul Bronze Low-e w/ Argon	0.29	0.29	Y
Awning	none	3/4"	Insul Low-e 240 w/ Argon	0.29	0.19	Y
Awning	none	3/4"	Zo-e-shield 5 w/ Argon	0.28	0.20	Y
Awning	none	3/4"	Zo-e-shield 6 w/ Argon	0.29	0.20	Y
Awning	none	3/4"	Zo-e-shield Coastal w/ Argon	0.29	0.20	Y
Awning	none	1"	Zo-e-shield 7	0.26	0.19	Y
Awning	none	1"	Zo-e-shield 7 w/ Argon	0.22	0.18	Y
Awning	Std GIA/SDL	3/4"	Insul Low-e w/ Argon	0.29	0.28	Y
Awning	Std GIA/SDL	3/4"	Insul Bronze Low-e w/ Argon	0.29	0.26	Y
Awning	Std GIA/SDL	3/4"	Insul Low-e 240 w/ Argon	0.29	0.17	Y
Awning	Std GIA/SDL	3/4"	Zo-e-shield 5 w/ Argon	0.28	0.18	Y
Awning	Std GIA/SDL	3/4"	Zo-e-shield 6 w/ Argon	0.30	0.18	Y
Awning	Std GIA/SDL	3/4"	Zo-e-shield Coastal w/ Argon	0.30	0.18	Y
Awning	Std GIA/SDL	1"	Zo-e-shield 7	0.26	0.17	Y
Awning	Std GIA/SDL	1"	Zo-e-shield 7 w/ Argon	0.23	0.17	Y
Awning	15/16" GIA	3/4"	Insul Low-e w/ Argon	0.29	0.25	Y
Awning	15/16" GIA	3/4"	Insul Bronze Low-e w/ Argon	0.29	0.24	Y
Awning	15/16" GIA	3/4"	Insul Low-e 240 w/ Argon	0.29	0.16	Y
Awning	15/16" GIA	3/4"	Zo-e-shield 5 w/ Argon	0.28	0.17	Y
Awning	15/16" GIA	3/4"	Zo-e-shield 6 w/ Argon	0.30	0.17	Y
Awning	15/16" GIA	3/4"	Zo-e-shield Coastal w/ Argon	0.30	0.17	Y
Awning	15/16" GIA	1"	Zo-e-shield 7	0.26	0.16	Y
Awning	15/16" GIA	1"	Zo-e-shield 7 w/ Argon	0.23	0.16	Y

Continued on the next page



Peachtree Doors and Windows is a manufacturer of exterior windows, patio doors and entrance doors. This Manufacturer's Certification Statement serves as verification that the Peachtree door and window products listed below qualify for the Energy Tax Credit in accordance with IRS 2006-26 document.

600 Series Fiberglass Clad Products						
Product Line	Grills	Glazing Thickness	Glazing Option	U-Factor	SHGC	Tax Credit
Casement Picture	none	3/4"	Insul Low-e 240 w/ Argon	0.28	0.21	Y
Casement Picture	none	3/4"	Zo-e-shield 5	0.30	0.23	Y
Casement Picture	none	3/4"	Zo-e-shield 5 w/ Argon	0.27	0.23	Y
Casement Picture	none	3/4"	Zo-e-shield 6 w/ Argon	0.28	0.23	Y
Casement Picture	none	3/4"	Zo-e-shield Coastal w/ Argon	0.28	0.23	Y
Casement Picture	none	1"	Zo-e-shield 7 w/ Argon	0.20	0.27	Y
Casement Picture	Std GIA/SDL	3/4"	Insul Bronze Low-e w/ Argon	0.27	0.29	Y
Casement Picture	Std GIA/SDL	3/4"	Insul Low-e 240 w/ Argon	0.28	0.19	Y
Casement Picture	Std GIA/SDL	3/4"	Zo-e-shield 5	0.30	0.21	Y
Casement Picture	Std GIA/SDL	3/4"	Zo-e-shield 5 w/ Argon	0.27	0.20	Y
Casement Picture	Std GIA/SDL	3/4"	Zo-e-shield 6 w/ Argon	0.29	0.20	Y
Casement Picture	Std GIA/SDL	3/4"	Zo-e-shield Coastal w/ Argon	0.30	0.21	Y
Casement Picture	Std GIA/SDL	1"	Zo-e-shield 7 w/ Argon	0.21	0.24	Y
Casement Picture	15/16" GIA	3/4"	Insul Low-e w/ Argon	0.27	0.28	Y
Casement Picture	15/16" GIA	3/4"	Insul Bronze Low-e w/ Argon	0.27	0.26	Y
Casement Picture	15/16" GIA	3/4"	Insul Low-e 240 w/ Argon	0.28	0.17	Y
Casement Picture	15/16" GIA	3/4"	Zo-e-shield 5	0.30	0.19	Y
Casement Picture	15/16" GIA	3/4"	Zo-e-shield 5 w/ Argon	0.27	0.19	Y
Casement Picture	15/16" GIA	3/4"	Zo-e-shield 6 w/ Argon	0.29	0.19	Y
Casement Picture	15/16" GIA	3/4"	Zo-e-shield Coastal w/ Argon	0.30	0.19	Y
Casement Picture	15/16" GIA	1"	Zo-e-shield 7 w/ Argon	0.21	0.22	Y
Direct Set	none	3/4"	Insul Low-e 240 w/ Argon	0.27	0.22	Y
Direct Set	none	3/4"	Zo-e-shield 5	0.30	0.24	Y
Direct Set	none	3/4"	Zo-e-shield 5 w/ Argon	0.26	0.24	Y
Direct Set	none	3/4"	Zo-e-shield 6 w/ Argon	0.27	0.24	Y
Direct Set	none	3/4"	Zo-e-shield Coastal w/ Argon	0.26	0.23	Y
Direct Set	Std GIA/SDL	3/4"	Insul Low-e 240 w/ Argon	0.27	0.20	Y
Direct Set	Std GIA/SDL	3/4"	Zo-e-shield 5	0.30	0.22	Y
Direct Set	Std GIA/SDL	3/4"	Zo-e-shield 5 w/ Argon	0.26	0.21	Y
Direct Set	Std GIA/SDL	3/4"	Zo-e-shield 6 w/ Argon	0.28	0.21	Y
Direct Set	Std GIA/SDL	3/4"	Zo-e-shield Coastal w/ Argon	0.28	0.21	Y
Direct Set	15/16" GIA	3/4"	Insul Low-e	0.30	0.29	Y
Direct Set	15/16" GIA	3/4"	Insul Low-e w/ Argon	0.26	0.29	Y
Direct Set	15/16" GIA	3/4"	Insul Bronze Low-e	0.30	0.28	Y
Direct Set	15/16" GIA	3/4"	Insul Bronze Low-e w/ Argon	0.26	0.28	Y
Direct Set	15/16" GIA	3/4"	Insul Low-e 240 w/ Argon	0.27	0.18	Y
Direct Set	15/16" GIA	3/4"	Zo-e-shield 5	0.30	0.20	Y
Direct Set	15/16" GIA	3/4"	Zo-e-shield 5 w/ Argon	0.26	0.19	Y
Direct Set	15/16" GIA	3/4"	Zo-e-shield 6 w/ Argon	0.28	0.19	Y
Direct Set	15/16" GIA	3/4"	Zo-e-shield Coastal w/ Argon	0.28	0.19	Y
Double Hung	none	3/4"	Insul Bronze Low-e w/ Argon	0.29	0.29	Y
Double Hung	none	3/4"	Insul Gray Low-e w/ Argon	0.29	0.27	Y
Double Hung	none	3/4"	Zo-e-shield 5 w/ Argon	0.28	0.20	Y
Double Hung	none	3/4"	Zo-e-shield 6 w/ Argon	0.29	0.20	Y
Double Hung	Std GIA/SDL	3/4"	Insul Low-e w/ Argon	0.29	0.27	Y
Double Hung	Std GIA/SDL	3/4"	Insul Bronze Low-e w/ Argon	0.29	0.26	Y
Double Hung	Std GIA/SDL	3/4"	Insul Gray Low-e w/ Argon	0.29	0.24	Y
Double Hung	Std GIA/SDL	3/4"	Zo-e-shield 5 w/ Argon	0.28	0.18	Y

Continued on the next page



Peachtree®

Doors and Windows

Performance Data & Information

Home Energy Efficiency Improvement Tax Credit

Manufacturer's Certification Statement

880 Southview Drive, Mosinee, WI 54455

Peachtree Doors and Windows is a manufacturer of exterior windows, patio doors and entrance doors. This Manufacturer's Certification Statement serves as verification that the Peachtree door and window products listed below qualify for the Energy Tax Credit in accordance with IRS 2006-26 document.

600 Series Fiberglass Clad Products						
Product Line	Grills	Glazing Thickness	Glazing Option	U-Factor	SHGC	Tax Credit
Double Hung	Std GIA/SDL	3/4"	Zo-e-shield 6 w/ Argon	0.30	0.18	Y
Double Hung	15/16" GIA	3/4"	Insul Low-e w/ Argon	0.29	0.25	Y
Double Hung	15/16" GIA	3/4"	Insul Bronze Low-e w/ Argon	0.29	0.23	Y
Double Hung	15/16" GIA	3/4"	Insul Gray Low-e w/ Argon	0.29	0.22	Y
Double Hung	15/16" GIA	3/4"	Zo-e-shield 5 w/ Argon	0.28	0.17	Y
Double Hung	15/16" GIA	3/4"	Zo-e-shield 6 w/ Argon	0.30	0.16	Y

Continued from previous page

Terms and Conditions:

Updated 01/08/10

Std GIA/SDL refers to 5/8" Grilles in the Airspace, 11/16" Grilles in the Airspace, and Simulated Divided Lite.

15/16" GIA refers to 15/16" Grilles in the Airspace.

All units are tested in accordance to National Fenestration Rating Counsel (NFRC) procedures. U-Factors are derived from computer simulations using WINDOW 5.2 and THERM 5.2 programs. Simulations are then verified by testing in accordance with NFRC 100-04.

The performance of windows and doors may be affected by factors beyond Peachtree's control, such as handling and installation, construction details of the building, exposure conditions, maintenance, normal wear and tear, migration of an inert gas from the insulated glass unit and the like. Ratings (for example, R or U-factors, infiltration tests, etc.) are for comparison purposes only. While Peachtree products are manufactured to meet or exceed published ratings, it is not possible to guarantee that they will meet or exceed those ratings after they have been installed, and this is specifically excluded from any warranty.

Under penalties of perjury, I declare that I have examined this certification statement, and to the best of my knowledge and belief, the facts are true, correct, and complete.

Emory Budzinski
Senior Product Manager